

Magnetboremaskine

Ekstra lav

ECO.36



Højden er kun

165 mm / 6 1/2"

Specifikationer

Kernebor



36 mm

1 7/16"

Hjørne



50 mm

2"

Højde



165 mm

6 1/2"

Vægt



10.3 kg

22.7 lbs

Motor



1050 W

9.6 A

Magnet



1200 kg

2645 lbs



Teknisk data

	Metrisk	Tommer
Kernebor	Ø 36 mm	1 7/16"
Undersænker	Ø 40 mm	1 9/16"
Hjørneboring	0°: 50 mm	2"
	90°: 53 mm	2 1/16"
	45°: 60 mm	2 3/8"
Længde	310 mm	12 3/16"
Bredde	135 mm	5 5/16"
Højde	165 mm	6 1/2"
Bevægelse	40 mm	1 9/16"
Vægt	10.3 kg	22.7 lbs
Magnet (lxbxh)	80x160 mm	3 1/8"x6 5/16"
Magnet kraft	1200 kg	2645 lbs
Motor	1050 W	9.6 A
Hastighed ubelastet	700 min ⁻¹	700 rpm
Hastighed belastet	400 min ⁻¹	400 rpm
	(1050 W)	(9.6 A)
Spindel	19,05 mm weldon	3/4" weldon
Volt	110 - 120 V AC / 50-60 Hz	
	220 - 240 V AC / 50-60 Hz	

Yderligere fordele:

- Brugervenligt quick-connect kernebor system
- Aftageligt skraldehåndtag til brug både venstre og højre side
- Aftagelig og flytbar op og ned af sikkerhedsafskærmning
- Integreret el-kabel
- Sikkerheds feste integreret

